



| dw  | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F   | J   | K    | L  | M    | N | do    | Whight<br>[Kg] |
|-----|----------------|-----------------------|------|----------------|-----|-----|-----|------|----|------|---|-------|----------------|
|     |                |                       |      | Min            | Max |     |     |      |    |      |   |       |                |
| 200 | 5              | 3                     | 3525 | 45             | 90  | 136 | 144 | 35.5 | 65 | 35.5 | - | 209.6 | 16             |

**Note:**  
 -Dynaminc Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |   |                     |
|--|---------------------------------------|---|---------------------|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <br><b>Rata Eng.</b> |                     |
|  | Title: <b>200 SPC-5</b>               |   |                     |
| Size: A4   | Revision:                             | Scale   | Sheet <b>1 OF 1</b> |
| Tel: +98 31 33 93 2334<br>Fax: +98 31 33 93 2335   |                                       | URL: www.rata-tech.com<br>Email: info@rata-tech.com   |                     |