



| dw  | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F   | J   | K  | L  | M  | N   | do  | Whight<br>[Kg] |
|-----|----------------|-----------------------|------|----------------|-----|-----|-----|----|----|----|-----|-----|----------------|
|     |                |                       |      | Min            | Max |     |     |    |    |    |     |     |                |
| 280 | 6              | 7                     | 3525 | 45             | 90  | 120 | 237 | 28 | 65 | 27 | 187 | 287 | 22.2           |

**Note:**  
 -Dynaminc Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |   |
|--|---------------------------------------|---|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <br><b>Rata Eng.</b> |
|  | Title: <b>280 SPB-6</b>               |   |
| Size: A4   | Revision:                             | Scale   |
| Tel: +98 31 33 93 2334   | URL: www.rata-tech.com                |   |
| Fax: +98 31 33 93 2335   | Email: info@rata-tech.com             |   |