



| dw  | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F  | J   | K    | L  | M    | N   | do  | Whight<br>[Kg] |
|-----|----------------|-----------------------|------|----------------|-----|----|-----|------|----|------|-----|-----|----------------|
|     |                |                       |      | Min            | Max |    |     |      |    |      |     |     |                |
| 300 | 4              | 7                     | 3020 | 25             | 75  | 82 | 257 | 15.5 | 51 | 15.5 | 144 | 307 | 21.2           |

**Note:**  
 -Dynamic Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |  |                            |
|--|---------------------------------------|--|----------------------------|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <b>Rata Eng.</b>  |                            |
|  | Title: <b>300 SPB-4</b>               |  |                            |
| Size: A4   | Revision:                             | Scale  | Sheet <b>1</b> OF <b>1</b> |
| Tel: +98 31 33 93 2334<br>Fax: +98 31 33 93 2335   |                                       | URL: www.rata-tech.com<br>Email: info@rata-tech.com  |                            |