



| dw  | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F   | J   | K  | L  | M  | N   | do  | Whight<br>[Kg] |
|-----|----------------|-----------------------|------|----------------|-----|-----|-----|----|----|----|-----|-----|----------------|
|     |                |                       |      | Min            | Max |     |     |    |    |    |     |     |                |
| 630 | 8              | 5                     | 4030 | 55             | 100 | 158 | 587 | 41 | 76 | 41 | 216 | 637 | 90             |

**Note:**  
 -Dynamic Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |   |                            |
|--|---------------------------------------|---|----------------------------|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <br><b>Rata Eng.</b> |                            |
|  | Title: <b>630 SPB-8</b>               |   |                            |
| Size: A4   | Revision:                             | Scale   | Sheet <b>1</b> OF <b>1</b> |
| Tel: +98 31 33 93 2334   |                                       | URL: <a href="http://www.rata-tech.com">www.rata-tech.com</a>   |                            |
| Fax: +98 31 33 93 2335   |                                       | Email: <a href="mailto:info@rata-tech.com">info@rata-tech.com</a>   |                            |