



| dw  | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F  | J   | K   | L  | M   | N   | do    | Whight<br>[Kg] |
|-----|----------------|-----------------------|------|----------------|-----|----|-----|-----|----|-----|-----|-------|----------------|
|     |                |                       |      | Min            | Max |    |     |     |    |     |     |       |                |
| 355 | 5              | 4                     | 3525 | 45             | 90  | 80 | 320 | 4.5 | 89 | 4.5 | 178 | 360.6 | 15.7           |

**Note:**  
 -Dynaminc Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |  |                            |
|--|---------------------------------------|--|----------------------------|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <b>Rata Eng.</b>  |                            |
|  | Title:<br><b>355 SPA-5</b>            |  |                            |
| Size: A4   | Revision:                             | Scale  | Sheet <b>1</b> OF <b>1</b> |
| Tel: +98 31 33 93 2334   |                                       | URL: <a href="http://www.rata-tech.com">www.rata-tech.com</a>  |                            |
| Fax: +98 31 33 93 2335   |                                       | Email: <a href="mailto:info@rata-tech.com">info@rata-tech.com</a>                                      |                            |