



| dw | N<br>(grooves) | Fig.<br>(Pulley Type) | TB   | d <sub>1</sub> |     | F  | J  | K  | L  | M | N | do | Whight<br>[Kg] |
|----|----------------|-----------------------|------|----------------|-----|----|----|----|----|---|---|----|----------------|
|    |                |                       |      | Min            | Max |    |    |    |    |   |   |    |                |
| 75 | 3              | 6                     | 1210 | 12             | 32  | 40 | 51 | 15 | 25 | - | - | 79 | 0.7            |

**Note:**  
 -Dynaminc Balancing at: 1500 rpm acc. to ISO 1940/1 Gr "6.3".  
 -V Pulley Phosphate Coated.  
 -All Dimension acc. to DIN 2211.

|  |                                       |  |                            |
|--|---------------------------------------|--|----------------------------|
| <br>ISO 128 | Material:<br><b>Ductile Cast Iron</b> | <b>Rata Eng.</b>  |                            |
|  | Title: <b>75 SPZ-3</b>                |  |                            |
| Size: A4   | Revision:                             | Scale  | Sheet <b>1</b> OF <b>1</b> |
| Tel: +98 31 33 93 2334   |                                       | URL: www.rata-tech.com   |                            |
| Fax: +98 31 33 93 2335   |                                       | Email: info@rata-tech.com  |                            |